

The background features a complex geometric design. It consists of several large, overlapping shapes that resemble stylized letters or architectural forms. These shapes are filled with a fine, light gray dotted pattern. The overall composition is minimalist and modern, with a focus on clean lines and a monochromatic color palette of white, light gray, and black.

# SHIELD

## About SHIELD



Constuction area is generally regarded as messy and noisy place because of noise and dust created from there.

However, thanks to SHIELD's well exprienced professioanlity, many construction areas have been changed into places that are cleaner and safer than before.

Our panels are produced and designed to completely block dust sand and any type of noise from construction and industrial area.

The importance of noise control has been increasing to ensure the life quality of people who live nearby as well as improve the image of the area.

Moreover, We are doing our best to make these area be naturally harmonized with surrounding so that the site does not ruin the overall urban design.

With SHIELD, construction area becomes safer, cleaner and a part of urban design.

**SHIELD**  
*SHIELD LTD.*

|    |                                     |
|----|-------------------------------------|
| 3  | About SHIELD                        |
| 4  | At a Glance                         |
| 8  | Introduction of GL Steel            |
| 12 | SHIELD Steel Noise Barrier 50T Type |
| 14 | SHIELD Steel Noise Barrier 30T Type |
| 23 | GL Steel Hoarding Panel             |
| 26 | Precoated Color Steel Fence         |
| 29 | GL Steel Fence                      |
| 30 | Window Panel                        |
| 32 | Recycable PVC Panel                 |
| 33 | Steel Pipe                          |



# PRODUCT OVERVIEW

With Exclusive Quality Steel Coil supplied by POSCO, Dongbu Steel, Dongkuk Steel, SHIELD's products are constantly under developing to meet the needs of global partners. Our Fianl Goal is to make the construction site be fully harmonized with surroundings. We are the team changing the general perception of the construction and infrastructure.



The following items are required for the hoarding of various types of construction area. Recently more and more rebuilding sites are increasing because of the buildings with old-condition which were built several decades ago. So it becomes common to create a rebuilding construction sites in the middle of city or residential area. Even though there have been relentless efforts of constructors to minimize the noise and dust from their sites, Noise and dust from construction area have become problematic these days. However, with SHIELD's professional panels specialized to solve these struggles, more and more construction areas have become cleaner and neater and quieter.



**Steel Noise Barrier**  
Pemanent and temporary noise absorbing sound proof wall with exceptional quality



**GL Steel Hoarding**  
Exclusive Quality Based on GL Steel Coil  
New Vision of Hoarding industry



**Pre-coated Steel Hoarding Panel**  
White-colored pre-painted panel specialized for reusing



**GL Steel Fence**  
Flat version of GL steel fence with unrivald lifespan and quality



**Window Panel**  
Transparent Panel for Additional Design



**RPP(Recycable PVC Panel)**  
Cost-effective hoarding that is widely used in every type of construction



## OUR COMPETITIVENESS

To become a professional in one certain field is never an easy task.

Also it cannot be achieved within several years  
SHIELD team has used its technological acumen and years of experience to solve the actual problem of our partners and has improved the conditions of construction area as well as the life quality of residents.



### Our Professionality based on experience

We have done the research, development and performances about the Noise and Dust control of the construction area since 2003.

We are the pioneer and leader of hoarding market in Korea. With our huge database, we can exactly catch what type of fence or hoarding is needed and what is the best solution to our partners.



### Coverage Capability

Depends on the site, different types of panels are needed. We can cover every type of sound and dust control panels from Permanent Sound Proof Wall to RPP hoarding for proper solution. With 20 years of accumulated database, we serve our clients the most appropriate item.



### Matchless Quality with Reasonable Price

Through our exclusive partnerships with POSCO, Dongbu Steel and Dongkuk Steel, we have been able to supply the panels to our partners with matchless quality and reasonable price. We do not compromise the quality of our steel coil. Made in Korea Steel coil is our identity, our speciality and the thing that makes us different.



### Customization

Our last competitiveness is our flexibility. We have encountered various needs of our partners. To meet every types of needs, our manufacturing lines are specialized for customization. We have served exact size, thickness, material what our partners exactly want and that is the key of our customer service.



## INTRODUCTION OF GL STEEL

GL is the brand name for 55% aluminum-zinc coated steel sheet produced by SHIELD. GL is generally known as Alu-Zinc in steel market. GL is highly heat and corrosion resistant, combining the properties of aluminum which renders increased durability, excellent heat resistance, and formability, and those of zinc which offers high heat resistance and excellent corrosion protection. GL is three to six times more corrosion resistant than regular galvanized steel sheet, with a 20-year lifespan for residential use.

### ALUMINUM

(Weigh Ratio : 55.0% / Capacity Ratio : 80%)  
For Long - term durability

### ZINC

(Weigh Ratio : 43.4% / Capacity Ratio : 19%)  
For Anti-corrosive ability

### SILICON

(Weigh Ratio : 1.6% / Capacity Ratio : 1%)  
For Heat-resistance

### Excellent Durability

GL is three to six times more corrosion resistant than zinc coated steel sheet of the same thickness. GL is backed by a 20-year life span for residential use by steel mill.

### Smooth Surface

GL is available in a delicate light silver spangle, so it is appropriate for decorative use.

### Heat Resistance

The capacity ratio of the aluminum in the coated layer of GL is high at over 80%. GL will withstand a prolonged temperature of 315 degrees Celsius without discoloration or oxidization.

### Excellent Workability

The workability of GL is similar to that of galvanized steel sheet. Its ability to suppress fine cracks on the coating layer enhances the durability of the treatment area.

### Heat Reflectivity

GL is highly energy efficient, with superior heat reflectivity and low heat consumption.

### Excellent Paintability

Paint is highly adhesive to the coated layer of GL steel sheet, compared to galvanized steel plates




# GL vs GI

## Durability


GL(SuperGalum®) is three to six times more corrosion resistant than regular zinc coated steel sheet. The shearing surface has superior corrosion and stretch resistance to aluminum coated steel sheet. GL is backed with a 20-year life span.

### Corrosion Test (Outdoor Exposure Test)


Galvanized steel is subjected to a continuous rate of corrosion, whereas the corrosion of GL tends to slow down over time. This outstanding corrosion resistance is attributed to the anti-corrosion properties in the coated layer.



Exposure test comparing levels of corrosion (test period: 13 years)



Salt spray test on GL(SuperGalum®) Steel Sheet




Results of exposure tests conducted in a coatal region (test period: 13 years)




## Heat Resistance

The capacity ratio of the aluminum in the coated layer of GL is high at over 80%. SuperGalum® will withstand a prolonged temperature of 315 degrees Celsius without discoloration or oxidization.

Rate of oxidization from continuous heat



Heat Resistance of GL Steel Sheet



## Heat Reflectivity

GL steel sheet boasts superior heat reflectivity, which produces increased energy efficiency, making it an excellent material for the interior of electronic home appliances. Used as a roofing material, GL will inhibit the rise of a building's temperature, thereby lowering the cost of air conditioning. Food storage buildings made with GL enjoy the additional benefit of having stored grains protected from quality change.


### Comparison of heat reflectivity by product

| Product                | Heat Reflectivity (%) |
|------------------------|-----------------------|
| GL Steel Sheet         | 70 ~ 75               |
| Galvanized Steel Sheet | 30 ~ 40               |

## Organic Coating Process

Our organic film treatment on the coated layer of the GL steel sheet, which is applied to the in-line coater, includes acryl resin organic film containing 1~2μm chromate. In comparison with the temporary corrosion resistant property of the conventional chromate applied in post-treatment, GL offers the following functions.

- High corrosion resistance
- Lubrication properties
- Paintability
- Anti-fingerprint properties



STEEL NOISE BARRIER - 50T



To find the most appropriate material, thickness, absorbing material, SHIELD has done its field research over 10 years. To find the most comprehensive Noise Barrier to cover all type of noise-creating area, our R&D team has applied every feedback and complaint of conventional noise barrier. Throughout these relentless effort, SHIELD Steel Noise Barrier has become the most appropriate product for our clients and partners in terms of performance, durability, installation and cost. SHIELD's research is still on its way to solve every type of noise and environmental issue and make the construction and industrial site cleaner, neater and quieter from the sight of citizens and clients. SHILED Steel Noise Barrier will lower the hurdle of the noise barrier and bring the better life quality for citizen all around the world.

SIZE

1980mm x 500mm x 50mm

STEEL(COIL) THICKNESS

Front : 1.0T GL / Back : 0.6T POSMAC (Customizable)

SOUND ABSORBING MATERIAL

GlassWool Nature(Water-Free) / Polyester

STC / NRC

32 / 0.95 (Customizable)

TEST REFERENCE (AUSSURED BY KOLAS / ilac · MRA)

ISO 10140 - 2:2010 / ASTM E 413 : 2016

ISO 354 : 2003 / ASTM C 423-17



KOREA MARINE EQUIPMENT  
RESEARCH INSTITUTE

Need of Noise Barrier



According to WHO research, noise is an underestimated threat that can cause a number of short and long-term health problems, such as for example sleep disturbance, cardiovascular effects poorer work and school performance, hearing impairment and even weakening of national defence. Noise has emerged as a leading environmental nuisance in the world and the public complains about excessive noise more and more often.

The WHO guidelines for community noise recommend less than 30 dB in bedrooms during the night for a sleep of good quality and less than 35 dB in classrooms to allow good teaching and learning conditions. The WHO guidelines for night noise recommend less than 40 dB of annual average outside of bedrooms to prevent adverse health effects from night noise. Installing Noise Barrier is not an optional task anymore but the necessary task.

CONSTRUCTION

Urban construction  
Reconstruction  
Industrial Construction

INFRASTRUCTURE

Highways  
Port / Airport  
Railroad

COMMERCIAL AREA

Shopping Center  
Amusement Park

RESIDENTIAL AREA

Village  
Apartment  
Condominium

INDUSTRIAL AREA

Factory  
Oil & Gas  
Plant / Mill

MILITARY

Barracks  
Hoarding Fence  
Hangar



STEEL NOISE BARRIER - 30T



SHIELD's Steel Noise Barrier has been representative item for us since 2003. Steel Noise Barrier is a future oriented product for hoarding system to minimize the noise and dust of every type of construction and industrial area. As more and more cities are becoming urbanized, the needs of noise control have been increasing. To meet the comprehensive needs of citizen, SHIELD's Steel Noise Barrier has been the right answer, and it has changed the general perception of construction area as well as hoarding system. Steel Noise Barrier 30T type is highly preferred by our global partners thanks to its exceptional resilience and durability and unrivaled corrosion-resistance comparing to every other noise barriers with GI steel by using GL with Alu-Zinc Coating.

|   |
|---|
| SIZE  |
| 1980mm x 500mm x 30mm                           |
| STEEL(COIL) THICKNESS - SuperGalum(GL)          |
| 0.5T (0.5mm)                                    |
| SOUND ABSORBING MATERIAL                        |
| Polyester                                       |
| STC / NRC                                       |
| 24 / 0.65                                       |
| TEST REFERENCE (AUSSURED BY KOLAS / ilac · MRA) |
| ISO 10140 - 2:2010 / ASTM E 413 : 2016          |
| ISO 354 : 2003 / ASTM C 423-17                  |



KOREA MARINE EQUIPMENT  
RESEARCH INSTITUTE

RECOMMENED USES

Since SHIELD's Steel Noise Barrier 30T type's easy installation and its exceptional performance, it is widely used in various type of area. It has been installed every types of places that create noises or dust from general construction area to military base. As

more and more people gain concerns about noise control the places that Steel Noise Barrier cover has been diversified. We have been constantly developed to cover those areas to meet the needs of partners who are seeking the most appropriate way to control the noise.

|   |  |                                      |
|---|--|--------------------------------------|
| CONSTRUCTION  | INFRASTRUCTURE                         | COMMERCIAL AREA                      |
| Urban construction<br>Reconstruction<br>Industrial Construction | Highways<br>Port / Airport<br>Railroad | Shopping Center<br>Amusement Park    |
| RESIDENTIAL AREA  | INDUSTRIAL AREA                        | MILITARY                             |
| Village<br>Apartment<br>Condominium                             | Factory<br>Oil & Gas<br>Plant / Mill   | Barracks<br>Hoarding Fence<br>Hangar |





## Why SHIELD Noise Barrier?



### Color painting

With Alu-Zinc coating at the surface not only make the panels more durable but also maximize its paintability. Colors are perfectly painted with high saturation. Colors improve the panel design, however prolong the lifespan and increase the heat resistance rate.

### Installation

With 50mm thickness. SHIELD steel noise barrier is designed as light-weight so that one person can lift it for installation without machine. It allows workers to easily install the structure and save the cost and effort of installation.

### Eco-friendly / Reusable Product

Whole cover of SHIELD steel noise barrier is made with steel. It is durable, long-lasting and rarely creates harmful substance like CO<sub>2</sub> or methane when it is produced, formed and scraped. Also, we also provide 100% natural substance named glass wool nature as an absorbing material. Since it is not transformed after installation, it can be reused in the other site.



## Product Layer of SHIELD Steel Noise Barrier

### PosMAC Steel Galley Type Back Plate

Magnesium-Aluminum-Zinc Alloy Coating Steel Panel, Much durable and stable than aluminum plate. Wider-designed gallery (Sound absorbing hole) allows it to effectively absorb sounds in any conditions.

### Glass Wool Nature / Polyester

Core of SHIELD Steel Noise Barrier 50T Type. Absorbs wide-range of noise and exactly reduce the noise by its exceptional quality. Eco-friendly material that does not produce pollution on its disposal. No risk of deterioration with special water-resistant coating.

### Sound Insulation Membrane Pad

Sound insulation membrane pad for additional insulation of sound as well as absorbing sound with main absorbing material. It is designed for perfect supporting to enhance its insulating ability.

### GL Steel Front Plate

Sophisticatedly designed front plate to prevent bending or physical damage. Perfectly protect the inner material and maintain the whole structure. Extremely durable and much more anti-corrosion with 55% Aluminum-Zinc coated steel.

### GL Steel Galley Type Back Plate



Aluminum-Zinc Alloy Coating Steel Panel, Extremely Durable and anti-corrosion compare to normal Galvanized Steel. Lightweight for easy installation and safety of workers. Wider-designed gallery (Sound absorbing hole) makes it effectively absorb sounds in any conditions.

### Polyester

Core of SHIELD Steel Noise Barrier 30T Type. Widely used sound absorbing material with fire-resistance feature.

### GL Steel Front Plate

Sophisticatedly designed front plate to prevent bending or physical damage. Perfectly protect the inner material and maintain the whole structure.





# Color Designed Steel Noise Barrier 30T type in Singapore

The importance of city beauty and urban design is still increasing. Singapore, one of the leading countries in the world is taking SHIELD's Steel Noise Barrier to reduce the noise and dust from construction area and make the construction site be part of city design. With exceptional quality with GL steel, our corrosion-resistance panel's color perfectly remains after years and years.



SHIELD has consistency proven itself to be a top supplier in Singapore. All of our panel is apporved by Singapore Land Transport Authority (LTA). Moreover, with our specialized customization service, SHIELD has created new spear shaped top panel for LTA project to effectively minimize the sound from transport system. Our ability of customization has solidfied our reputation and capability meeting the various needs from our global partners.



01  
02


03  
04  
05

- ① Singapore Design Panel near residential area
- ② Singpaore LTA project with TNB panel on top
- ③ Singapore Holding Ian project
- ④ Singapore Jalan Angin Laut Playground site
- ⑤ Singapore Obayashi project near residential area



# Galvanized Color Steel Noise Barrier 30T type in South Korea

In Korea, it is common to watch Galvanized Color Steel Noise Barrier 30T type in everywhere. In 2018, the number of official civil complaint regarding noise control exceeded 28,000. And it is rapidly growing since the importance of life quality and privacy has been stressed. So, it is common to install noise barrier in every type of construction and industrial site. SHIELD has been the leading solution provider of every type of noise issue in Korea.



- ① Namhan Highschool remodeling area
- ② Woosung reconstruction site with dust net on top
- ③ Namwon laboratory construction site
- ④ Kyeonggi Lotte Mart Parking lot noise control



## Anti Dust Net

To effectively control the dust blown from construction or industrial site, SHIELD has provided the additional Anti Dust Net to partners as an option. Anti Dust Net is also easy to install and maximize the dust control in addition to the Noise Barrier structure.





We think fencing and hoarding industry needs fundamental changes. It needs to be changed into more eco-friendly and user friendly way. Even though we have had other options SHIELD has persisted in using GL Steel instead of using any other materials. Because of GL steel's exceptional performance of durability, lifespan and flawlessness, We have concluded that GL is the most future-based and eco-friendly product for our partners. Thanks to our tenacious research and development of GL steel, We have succeeded in producing GL steel into fence form with competitive price. SHIELD's GL Hoarding is gaining its reputation because of its performance and spreading all around the world

## GL Steel Hoarding Panel



### SIZE

Length :  
1000mm ~ 4000mm

Width : 530 mm

### THICKNESS

0.45T ~ 1 T (0.45mm ~ 1.0mm) GL Steel

### Unrivaed Durability

Unbreakable material with customizable thickness

55% Aluminum-Galvanized to maximize anti-corrosotion to extend lifespan

Expected lifespan : Over 20 years

### RECOMMANDED USE

1. Hoarding for Construction and Industrial Site
2. Partition in any type of area

### Anti-Corrosion

3-6 times more durable than normal galvanized steel in terms of corrosion rate.

### Easy to deploy

Do not need heavy supports, can be deployed only with steel pipe with hook

### Reusability

20 years of expected lifespan, elaborately designed for reusing

### Eco-friendly Product

Perfect replacement of Plastic or PVC hoarding even with much better performance






# Safe, Clean Construction Work Starts with SHIELD, is completed by SHIELD

Deploying Steel Fence means beginning of the work in construction.  
 Disassembling Steel Fence means completion of the work.  
 Steel Fence should stand still from the beginning to completion.  
 So it must be strong and durable enough to protect the pedestrian and workers for safety.  
 SHIELD GL Steel Panel is designed to perfectly protect the people and property with durability.  
 With customizable thickness, it can hold and protect workers from most type of general collision,  
 And help architect and workers be fully concentrate on their work by blocking the external influences.

## Comparson between conventioanl Hoarding system and SHIELD GL Steel Hoarding System



- Can be deployed in **any type** of ground surface
- Fully Cover** the construction area
- Cost effective** with own installation system
- Easier to store** and does not need a lot of space



- Can only be delployed in **flat** surface
- Can be **seen through** the under gap
- Cost more** because of its steel frame
- Take more space** because of its size



- PyungTaek new town project
- Gangbuk medical center rebuilding project
- GL Steel Fence with Holding Gate - Yangju Citizen library project

01

02

03





# Prepainted Color Steel Fence



## SIZE

Length :  
1000mm ~ 6000mm

Width : 530 mm

## THICKNESS

0.6 ~ 1.2 T (0.6 ~ 1.2mm)  
Sunclean

## RECOMMENDED USE

1. Hoarding for Construction and Industrial Site
2. Steel based Sandwich Panel
3. Physical advertisement Structure in industrial complexes

SHILED's Pre-coated Steel Hoarding Panel is an exclusive item of SHIELD based on Dongbu Steel's Anti-Pollution pre-coated Steel Coil(Sunclean). This product is specialized for reusing and the exact competitive good for PVC hoarding. It has minimum 10 years of life span and the whole installation structure of panel is finely designed to reuse it. In Japan, it is common to use steel hoarding more than decade to decrease the use of plastic. Our Pre-coated Steel Hoarding Panel provides a new vision and eco-friendly movement of overall hoarding industry.




# SunClean / Anti-Pollution Precoated Steel

Excellent resistance against oxidation and alkalization. Optimal choice for panel Materials or factory exteriors. High surface quality against pollutions including sulfurous acid gas in comparison with conventional prepainted steel. Easy maintenance when cleaning buildings Due to super anti-pollution features compared with conventional pre-painted steel. Outstanding weather resistance.


## Carbon black pollution assessment results

Sunclean has been proven to possess the greatest anti-pollution properties, showing the least amount of change in color in comparison with conventional steel sheet.

- Drop 0.5% carbon black solution on the Sunclean product and heat at 80 ° C for 24~48 hours. Wash with water and examine the color difference.



## Section of Product



## Applied Material

- Galvanized (GI)
- 55% Aluminum SuperGalum(SGL)
- Aluminum (Al)
- Stainless Steel (SUS)




## Pre-coated Steel Hoarding Panel

- Exceptional Life Span at least 10 years
- Applied Anti-Pollution Material to maximize reusability
- No risk of breaking, decoloration
- Echo Friendly Product perfectly replaces the plastic hoarding system
- Perfect flatness for easy attachment of advertisement
- Always maintain strong structure in multiple uses



## GL Steel Fence



### SIZE

Length :  
1000mm ~ 6000mm


Width : 530 mm

### THICKNESS

0.6 ~ 1.2 T (0.6 ~ 1.2mm)  
GL Steel

### Feature

1. Galvanized color Steel Hoarding Panel
2. Cost effective product compares to Pre-coated Steel Hoarding Panel
3. Eco-friendly product perfectly replace current plastic hoarding system



- ① Wirye LH Korea Land Housing Corporation Project
- ② PyeongChang Seoul National University extension Project
- ③ PyeongChang Seoul National University extension Project



### SHIELD RS Joiner

SHIELD's RS Joiner is an accessory for Pre-coated Steel Hoarding Panel to maximize its reusability. RS joiner does not ruin or screw up the panel so the panel can be fully preserved after deployment for next use.



# Window Panel



## SIZE

Length : 1980 mm  
Width : 495 mm

## Transparent Material

Polycarbonate

## RECOMMENDED USE

1. Transparent Hoarding for Construction and Industrial Site
2. Partial Design among Steel Noise Barrier structure

SHIELD Window Panel is exclusive item that is only produced in SHIELD. Window Panel is design to effective see through the inside of the working area. It makes the working area be harmonized with surrounding so that increase the image of the area. SHIELD Window Panel is also designed with Steel Frame for its durability and Noise insulation ability.



## WINDOW PANEL VERTICAL TYPE FOR HOARDING

1. Transparent Hoarding for Construction and Industrial Site
2. Partial structure for design and safety



01

02

03

- ① Singapore Stevens Area Window Panel with Steel Noise Barrier - 30T type
- ② Window Panel on top of Color Steel Panel with Anti-dust Net
- ③ Window Panel beside side walk - Seongnam urbanization area



RPP(Recycable PVC Panel)



SIZE

Length :  
2000mm~6000mm  
Width : 670 mm

THICKNESS

30mm

RECOMMENDED USE

- 1. Design Hoarding for Construction and Industrial Site
- 2. Hoarding Fence with the effect of advertisement

SHIELD Recycable PVC Panel is a complex panel for temporary fence to improve construction method, construction cost saving and urban looks at the same time with the creation of space layer and excellent effect of sound insulation based on major material of PVC reinforced plastic.

Strong Points

- 1. Products with good performance differentiated from existing products due to the maximized special layer
- 2. Easy construction and economics with light products
- 3. Smooth surface and easy advertisement work
- 4. Good urban looks with the representation of various colors
- 5. Easy maintenance in damaged products and recyclability
- 6. No worry of transformation and de-colorization with improved stability of materials
- 7. Securing the safety of pedestrians and easy block of sound and dirt



01

02

- ① Byulnae New Town Project
- ② Singapore Sentosa Siloso Beach area

STEEL PIPE



SIZE / SPECIFICATION

Outer Diameter(Round) : 48.6 mm  
Thickness : 2.3 T (2.3 mm)  
Length : 6M

Usage

Horizontal Support for Steel Noise Barrier - 30T  
Support for GL Steel Hoarding  
Any type of Hoarding and Scaffolding

Steel Pipe is basic item for every type of construction or industrial area. It can be used from support for SHIELD Steel Noise Barrier - 30T type to Scaffolding. SHIELD Steel Pipe is also manufactured from made in Korea Steel from POSCO, Hyundai Steel and rolled and tailored by SHIELD's well-experienced technique. It can also be customized from 1M to maximum 6M. For special structures, SHIELD's pipe grafts cold rolling technology creates a plastic working hardening effect which is one of the strengthening mechanisms of steel. Its strength is improved by 10~30% through hardening of steel by conducting special rolling plastic working on one side of a skelp. It can also secure an elongation with a special shape inside a pipe and save materials by being elongated toward the direction of the width and the length of a skelp by special roll rolling work. At the time of this cold rolling work, strength improvement of steel materials secure required strength necessary for using even though materials become lighter as tensile strength and compression strength increase to 10~30% due to refining of internal tissues of steel by rolling (tissue densification), and work hardening by strength improvement by texture and work hardening by pile-up of dislocation inside metal tissues of steel.

Key Feature of SHIELD Steel Pipe

Light Weight


Preventing construction workers' musculoskeletal disease, and improving their work efficiency

Solidity

Enduring external forces well due to high strength

Compatibility


Excellent compatibility with other companies' pipes




- ① Support for Steel Noise Barrier - 30T type
- ② Support for GL Steel Hoarding
- ③ Steel Pipe tighten by RS joiner
- ④ Steel Pipe tighten by RS joiner
- ⑤ Scaffolding Clamp
- ⑥ H-beam Clamp




COLOR CHART




2-155 GLOSS WHITE  
FRM557 PE100 RAL9010  
#2014(K)



2-145 MATT WHITE  
EP300 9904 WHITE(SHI)



2-60 BLACK  
FEC033 EP119 BLACK  
G-60(MK)



2-61 YELLOW  
FEM802 EP100 YELLOW  
(WJ)



2-67 ORANGE  
FEN202 EP100 ORANGE  
(ESS)



2-173 RED  
FRL461 PE120 MAHNDRA  
RED (DY)



2-78 PINK  
FEO367 EP100 KR PINK  
(SRC)



2-79 SKY BLUE  
FEH051 EP100 BLUE  
(DWP)



2-172 BLUE  
FRL419 PE120 97C/BUE  
(SWS)



2-84 DARK BLUE  
FEL894 EP119 D/BUE  
(SH)




2-170 LIGHT GREEN  
FRL447 PE120 9902  
LIGHT GREEN (SHP)



2-96 DARK GREEN  
FEN024 EP100 GREEN  
(DHP)




2-171 EVER GREEN  
FRL477 PE120 EVER  
GREEN (SH)



2-166 LIGHT GREY  
FRL855 PE200 5BG  
7.0/0.4 (HS)



2-167 GREY  
FRL743 PE120 LPG GREY  
#HJ



2-159 IVORY  
FRR038 PE120 E-32871  
(SH)

\* MORE COLORS CAN BE PROVIDED

SHIELD

SHIELD’s expert techincal team is ready to provide  
the best solution to its customers.

Email

info@shield-korea.com  
sales@shield-korea.com

Web Site

www.shield-korea.com

CONTACT

Head Quarter

www.shield-korea.com  
227, Toegye-ro, Jung-gu, Seoul,  
Republic of Korea  
TEL) +82 2 2269 1233  
FAX) +82 2 2285 1236


Yangju 1st Factory

201-11, Gwangjeok-ro,  
Gwangjeok-myeon, Yangju-si,  
Gyeonggi-do, Republic of Korea  
TEL) +82 31 855 2300  
FAX) +82 31 676 1236

Yangju 2nd Factory

287, Jungang-ro,  
Baekseok-eup, Yangju-si,  
Gyeonggi-do, Republic of Korea  
TEL) +82 31 872 1235





SHIELD